

A7-183/10

Natural Rubber Based Adhesive

Description

A7-183 is a solvent based natural rubber adhesive.

Due to its flexible and moisture resistance properties, the adhesive is suitable for the seam sealing and waterproofing of outdoor clothing and equipment.

This provides a much quicker method of manufacture or repair than additional stitching or patching.

Application method(s)

Surfaces should be clean, dry and free from dust and grease.

Curing

Self curing due to solvent evaporation.

Usage Notes

Clean equipment with Naptha.

Thinning is not necessary.

Health & Safety

See SDS. If you need a copy of the latest version please contact sales@itac.uk.com.

Packing and Storage

25 litre open top pails and 200 litre open top drums.

Store in a cool dry place between 5°C and 30°C.

Typical properties for this product are given based on ITAC manufacturing experience. They are not a specification of the product.

ITAC Limited,
Bankfield Mills, Bankfield Street,
Stoneclough, Radcliffe,
Manchester M26 1AS

Tel: + 44 (0)1204 573736
email: sales@itac.uk.com
web: www.itacadhesives.com

Reg in Eng No 499145
VAT reg No 145 4337 73





A7-183/10

Natural Rubber Based Adhesive

Typical Properties	Value	Units	Test method
Base Polymer	Natural Rubber	NA	
Colour	Buff neutral	NA	
Specific Gravity	0.89	NA	
Solvent(s)	Mix of aliphatic and aromatic hydrocarbons	NA	
Solids Content	24 - 28	% by weight	
Viscosity	2,200,000-2,600,000	cPs	Brookfield with Helipath Spindle T96 Speed 1 at 20°C.
Flashpoint	18.5	°C	Closed Cup, ISO 3679
Shelf life	12 months from date of manufacture, which is printed on the label.		

Other Properties	Value	Units	Test Method

Typical properties for this product are given based on ITAC manufacturing experience. They are not a specification of the product.

ITAC Limited,
Bankfield Mills, Bankfield Street,
Stoneclough, Radcliffe,
Manchester M26 1AS

Tel: + 44 (0)1204 573736
email: sales@itac.uk.com
web: www.itacadhesives.com

Reg in Eng No 499145
VAT reg No 145 4337 73

