

C3-384/3

One Pack Polyurethane Coating



Description

C3-384 is a one pack polyurethane solution which provides good resistance to hydrolysis and a dry handle for a tack free finish.

Its flexible properties, high tensile strength, high lightfastness, moisture and UV resistance make it a suitable coating for many outdoor building and industrial applications where a tough and durable finish is required.

Application method(s)

C3-384 can be applied onto textiles by the usual knife coating techniques ie; air-knife, knife over roller and knife over blanket.

Curing

Solvent is to be removed by zone drying. Typical zones would be 70°C, 90°C and 120°C.

Usage Notes

Clean equipment with toluene.

Thinning is not necessary.

Health & Safety

See SDS. If you need a copy of the latest version please contact sales@itac.uk.com.

Packing and Storage

25 litre open top pails.

Store in a cool dry place between 5°C and 30°C.

Typical properties for this product are given based on ITAC manufacturing experience. They are not a specification of the product.

ITAC Limited,
Bankfield Mills, Bankfield Street,
Stoneclough, Radcliffe,
Manchester M26 1AS

Tel: + 44 (0)1204 573736
email: sales@itac.uk.com
web: www.itacadhesives.com

Reg in Eng No 499145
VAT reg No 145 4337 73



C3-384/3

One Pack Polyurethane Coating

Typical Properties	Value	Units	Test method
Base Polymer	Polyurethane	NA	
Colour	Natural	NA	
Specific Gravity	0.92	NA	
Solvent(s)	Toluene/Isopropyl alcohol	NA	
Solids Content	23 - 25	% by weight	
Viscosity	3,000-5,000	cPs	Brookfield Spindle 5, Speed 10 at 20°C.
Flashpoint	5.5	°C	Closed cup, ISO 3679
Shelf life	12 months from date of manufacture, which is printed on the label.		

Other Properties	Value	Units	Test Method

Typical properties for this product are given based on ITAC manufacturing experience. They are not a specification of the product.

ITAC Limited,
Bankfield Mills, Bankfield Street,
Stoneclough, Radcliffe,
Manchester M26 1AS

Tel: + 44 (0)1204 573736
email: sales@itac.uk.com
web: www.itacadhesives.com

Reg in Eng No 499145
VAT reg No 145 4337 73

